

# STREET/STRIP

## PROCHARGER SUPERCHARGER SPECIFICATIONS



	A-1P	A-1R	B-1	CS-1	C-1	C-2	C-1R	P600B	P-1SC	P-1SC-1	P-1X	P-1SC-2	D-1	D-1SC	D-1X
<b>VOLUTE DIAMETER</b>	7"	7"	7"	7"	7"	7"	8"	9"	9"	9"	9"	9"	9"	9"	9"
<b>MAX SUPERCHARGED HP</b>	100	150	250	550	675	725	675	775	825	825	875	825	925	925	1000
<b>MOTOR BASE HP RANGE*</b>	25-75	50-95	60-150	150-325	150-325	175-375	150-325	200-500	200-500	200-450	300-500	200-450	300-500	300-500	300-550
<b>MAX FLOW (CFM)</b>	200	450	600	900	1,000	1,000	1,000	1,150	1,200	1,200	1,275	1,200	1,400	1,400	1,500
<b>MAX BOOST (PSI)</b>	15	15	20	24	24	24	30	24	30	32	32	30	32	32	32
<b>INLET HOSE DIAMETER</b>	3"	3"	3"	3.5"	3.5"	3.5"	4"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"	3.75"
<b>INDUCER DIAMETER</b>	2.02"	2.28"	2.28"	2.66"	2.75"	3.14"	2.83"	3.37"	3.37"	3.37"	3.57"	3.24"	3.37"	3.37"	3.57"
<b>EXDUCER DIAMETER</b>	4"	3.2"	3.2"	3.7"	4.25"	4.25"	3.89"	6.25"	6.25"	5.25"	5.56"	6"	6.25"	6.25"	6.20"
<b>OUTLET HOSE DIAMETER</b>	2"	2"	2"	2.5"	2.5"	2.5"	3"	3"	3"	3"	3"	3"	3"	3"	3"
<b>OUTLET I.D.</b>	1.75"	1.75"	1.75"	2.12"	2.12"	2.12"	2.60"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"	2.62"
<b>MAX IMPELLER RPM</b>	75,000	75,000	110,000	80,000	80,000	80,000	110,000	60,000	62,000	65,000	65,000	60,000	65,000	62,000	62,000
<b>INTERNAL STEP-UP</b>	4.11:1	4.11:1	4.95:1	8.30:1	4.70:1	4.70:1	4.70:1	3.05:1	4.10:1	4.10:1	4.10:1	4.10:1	4.44:1	4.10:1	4.10:1
<b>REVERSE ROTATION OPTION</b>	Only	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>SELF CONTAINED</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	No	Yes	Yes
<b>OIL CAPACITY</b>	2.5 oz	2.5 oz	2.5 oz	3.2 oz	2.5 oz	2.5 oz	2.5 oz	-	6 oz	6 oz	6 oz	6 oz	-	6 oz	6 oz

**BOLT ON 50-85% MORE POWER ON PUMP GAS WITH INTERCOOLED PROCHARGER KITS**

*See Other Side for F-Series Supercharger Specs*

03/19

CALL US FOR A DEALER NEAR YOU

(913) 338-2886

PROCHARGER.COM



#PROCHARGER

INVENTED, ENGINEERED, MADE IN THE USA

